

水神

Suijin Investments Ltd

BRINGING INFORMATION
TO WATER EFFICIENCY



ECOLight water-saving hand shower

with **isoflow**




- 3 minutes of showering (30 litres) green illumination
- 2 minutes (up to 50 litres) yellow illumination
- 1 minute (up to 60 litres) red illumination
- Then flashing red

With the ECOLight you will shower “greener”. The water-saving hand shower ECOLight signalizes by the LED-illuminated showerjet, how much water and how much time you have consumed already.

No batteries required. The energy for the LEDs is generated with a newly developed, quiet generator which is integrated in the shower head.

With memory function. The already used time can be saved for up to 2 minutes if the user interrupts the water supply. When turning on the water supply again it continues counting down.

Best comfort and low water consumption. The ECOLight is powered by the unique **isoflow** valve. This worldwide patented valve regulates the flow of water to exactly 10 litres per minute regardless of the water pressure - so you always shower with the optimum water flow. In addition to its precision the **isoflow** valve is characterized by minimal noise and longevity.



CERTIFIED



水神

Suijin Investments Ltd

BRINGING INFORMATION
TO WATER EFFICIENCY

ECOLight water-saving hand shower

Dimensions:



What is *isoflow*?

isoflow has an unique, patented design. The O-ring is not exposed to the water but is protected by the two adjusting elements, which provide for the variable opening. Thus it combines precise flow rate control with low noise and long service life.

Spray pattern:



Models:

model	item	isoflow
S125	ECOLight	8 litres per minute

Technical specifications:

scope of delivery	1x gasket 19 x 13 x 2 mm EPDM 1x gasket 18,5 x 12 x 1,5 mm fiber composite
materials	ABS, chrome-plated
tests & standards	complies with the requirements of TrinkwV
guarantee	1 year

CERTIFIED

